



**000257550 -  
000257557**

#### GENERAL

ceiling  
suspended  
black  
IP20  
direct 50000 lm  
indirect 8000 lm  
RAL 9005\*

#### LED

4000K  
CRI  $\geq$  80  
L80/50000h  
initial  $\leq$  3 MacAdam

#### OPTICAL

beam angle 44° (direct)  
clear cover (indirect)

#### DIMENSIONS

cable 5000 mm  
length 1500 mm  
width 1500 mm  
height 200 mm  
tilt (SASSO) max. 40°  
weight 54 kg

#### ELECTRICAL

DIM DALI (HDTV-compatible)  
600 W (480 W direct/120 W indirect)  
97 lm/W  
12 DALI addresses  
PC1 220-240 V

\*RAL Palette colours may deviate slightly due to production conditions



Square light fitting made of extruded aluminium profile; seamlessly welded; surface black; suspended luminaire with 5000 mm cable suspension; with integrated tool-less suspension height adjustment; luminaire ball proof version to 57710 part 13/VDE 0710 part 13; spotlight with highly reflective aluminium reflector for improved thermal management; technology for maximum efficiency; no multiple shadows; light colour 4000K; Binning initial  $\leq$  3 MacAdam; CRI  $\geq$  80; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; precise radiation characteristic with 44° beam (direct light component); indirect component covered with clear acrylic glass; degree of protection IP20; PC1 220-240 V; DALI dimmable (HDTV-compatible)

